

Our Customers Say,
"Graffiti Master Products are the best I have ever seen"



Graffiti Master® - Making the World A Better Place!

MATERIAL SAFETY DATA SHEET

Graffiti Master
1813 Rutan Drive
Livermore, CA 94550

Daytime Phone: 800-447-2334
Technical Support: 888-534-7374
Emergency: Chemtel 800-255-3924

Date Compiled: 24 January 2001

SECTION 1: PRODUCT IDENTIFICATION

Product name: Plasti-Master

Synonym/Chemical name/Common name: Solvent Cleaner
DOT hazard class: Flammable material
Proper shipping name: Flammable liquid N.O.S. UN 1993, PKG GP II
(Contains Isopropyl alcohol)

SECTION 2: INGREDIENT INFORMATION

Hazardous Ingredients	Wgt %	Toxicity Data
Isopropyl Alcohol CAS# 67-63-0	TRADE SECRET	TLV=983 mg/m ³
Butyl Cellusolve CAS# 111-76-2	PER CFR	TLV=121 mg/m ³
Propylene glycol Monomethyl ether CAS# 107-98-2	1910.1200	TLV=369 mg/m ³

This product contains no chemical at a level which poses a significant risk as defined by California Proposition 65.

This product contains no toxic chemical, above its de minimis concentration, subject to reporting requirements of Title III SARA, section 313 EPCRA (40 CFR 372).

SECTION 3: PHYSICAL CHARACTERISTICS

Specific Gravity (H₂O=1): 0.86
Vapor pressure: 31.2 mm Hg
Vapor density (Air=1): >1
Percentage volatile by weight: 97
Solubility in water: Complete
pH (Undiluted): N/A
Evaporation rate (H₂O=1): >1
Freezing point: N/D
Boiling point: 181° F
Appearance and odor: Clear Liquid with distinct alcohol odor

SECTION 4: FIRE AND EXPLOSION HAZARDS

Flash point: 55o F
Flash point test method: TOC
Flammability limits: 2% to 12.7%
Extinguishing media: Water, Foam, CO2
Special fire fighting procedures: None
Unusual fire or explosive hazards: None

SECTION 5: REACTIVITY DATA/CONDITIONS TO AVOID

Stability: Stable
Incompatibilities (Conditions to avoid): None are known
Hazardous decomposition products: None
Hazardous polymerization will not occur.
Conditions to avoid: None

SECTION 6: HEALTH HAZARDS/FIRST AID

Primary routes of entry: None
Signs and symptoms: Sprayed mists may be irritating to eyes. Material may be irritating to sensitive skin and harmful or fatal if swallowed.
First aid procedures: For eye contact, flush with large amounts of water for at least 15 minutes. If irritation persists, contact a physician. For skin contact, flush with large amounts of water. If swallowed do not induce vomiting. Give two glasses of water and juice of oranges or lemons. Contact a physician.
There are no known chronic health effects caused by the use of this product.

SECTION 7: PERSONAL PROTECTION RECOMMENDATIONS

Respiratory protection: None
Ventilation: Use with adequate ventilation
Protective gloves: Neoprene gloves are recommended for long or repeated contact
Eye protection: Guard against eye contact.

SECTION 8: STORAGE/SPILL/SPECIAL HANDLING INFORMATION

Steps to be taken in case of spill: Remove all sources of ignition. Remove material with mops or absorbent material or flush area with water.
Waste disposal: Follow all local, state, and federal waste disposal regulations.
Special storage or handling precautions: Do not store near fire or flame.

N/D = Not determined N/A = Not applicable

This Material Safety Data Sheet is written and provided in good faith for the sole purpose of providing information for the safe use and handling of this product. It is compiled from technical data believed to be current and correct. It should not be taken as a warranty or representation for which Graffiti Master or S.D.L. Distributing assumes any legal responsibility. The buyer assumes all responsibilities of using and handling the product in accordance with local, state, and federal regulations.

Manufactured by Graffiti Master Products. All rights reserved.
Technical Support 888-534-7374 Sales 800-447-2334