



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 1 of 10

1. IDENTIFICATION

PRODUCT NAME: ICE FOE®
CAS #: MIXTURE

MANUFACTURER: OSSIAN INC., 635 SOUTH ELMWOOD AVE, DAVENPORT, IOWA 52802
EMERGENCY PHONE: 800-553-8011

PRODUCT USE: Ice Melting
USES ADVISED AGAINST: De-icing of concrete less than one year old. De-icing of metal surfaces.

2. HAZARD(s) IDENTIFICATION:

EMERGENCY OVERVIEW:

MAJOR HEALTH HAZARDS: CALCIUM CHLORIDE CAUSES EYE AND SKIN IRRITATION. HARMFUL IF SWALLOWED. MAY BE HARMFUL IN CONTACT WITH SKIN

PHYSICAL HAZARDS: Heat is generated by Calcium Chloride when mixed with water or aqueous acid solutions.

PRECAUTIONARY STATEMENTS: Wash thoroughly after handling.

GHS CLASSIFICATION OF MIXTURE:

CONTACT HAZARD – SKIN:	Category 2 – Causes skin irritation.
CONTACT HAZARD – EYE:	Category 2B – Mild irritant.
ACUTE TOXICITY – INHALATION:	No data available. Not classified.
ACUTE TOXICITY – ORAL:	Category 4 – Harmful if swallowed.
ACUTE TOXICITY – DERMAL:	Category 5 – May be harmful in contact with skin
CARCINOGENICITY:	Not classified as a carcinogen per GHS criteria. Not classified as a carcinogen by NTP, IARC, or OSHA

GHS LABELING PICTOGRAM:



GHS SIGNAL WORD:

WARNING

HAZARD STATEMENT: Non-toxic. No adverse health effects are anticipated with normal use of this product.

PRECAUTIONARY STATEMENT:

EYE CONTACT: Low irritant. Exposure may result in mild irritation. Can cause redness and pain.
INHALATION: Dust may cause irritation to upper respiratory tract (nose and throat).
SKIN CONTACT: Brief contact is essentially nonirritating to skin. Prolonged contact to calcium chloride in product may cause skin irritation, even a burn. Not classified as corrosive to the skin according to DOT guidelines. May cause more severe response if skin is damp. May cause more severe response if skin is abraded (scratched or cut). May cause more severe response on covered skin (under clothing, gloves).



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 2 of 10

INGESTION: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Swallowing may result in gastrointestinal irritation or ulceration.

OTHER HAZARDS: No other hazards known

3. COMPOSITION

SUBSTANCE/MIXTURE: Mixture.

<u>CHEMICAL NAME</u>	<u>PERCENTAGE</u>	<u>CAS NUMBER</u>
Calcium Chloride	> 90 < 92	010043-52-4
Water	> 4 - < 6	007732-18-5
Potassium Chloride	> 2 - < 3	007447-40-7
Sodium Chloride	> 1 - < 3	007647-14-5
Accelerating Agent(s)	< 1	N/A

TECHNOLOGY: Chemical properties of accelerating agents have been withheld as a trade secret. Accelerating agents covered under U.S. Patent – additional patents may be pending.

4. FIRST-AID MEASURES:

FIRST AID INHALATION: Remove to fresh air. Get medical attention for any breathing difficulty.

FIRST AID SKIN: Wash with soap and water. Obtain medical attention if irritation persists.

FIRST AID EYE: If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs, get medical advice/attention.

FIRST AID INGESTION: If swallowed, rinse mouth. Contact a poison control center or doctor/physician if you feel unwell. Never give anything by mouth to an unconscious or convulsive person.

Most Important Symptoms/Effects (Acute and Delayed):

Acute Symptoms/Effects: Listed below.

Inhalation (Breathing): Inhaling dust may cause irritation to upper respiratory tract (nose and throat).

Skin: Skin irritation. Direct abrasion of skin from solid, erythema and burn from reaction with water.

Prolonged contact and occlusion may cause more severe symptoms. Damage is localized to contact areas.

Eye: Eye Irritation. Direct abrasion of cornea from solid, erythema and burn from reaction with water, conjunctival swelling and cornea opacification from hypertonic solution and heat.

Ingestion (Swallowing): Consumption of solids or hypertonic solutions causes nausea, vomiting, and increased thirst.

Delayed Symptoms/Effects:

Chronic exposure to skin and mucus membranes that cause irritation may cause a chronic dermatitis or mucosal membrane problem

Interaction with Other Chemicals Which Enhance Toxicity: None known.

Medical Conditions Aggravated by Exposure: Any skin condition that disrupts the skin, such as abrasions, cuts, psoriasis, fungal infections, etc. Any upper respiratory conditions that compromise mucosa can increase local damage from dust contact. Any eye condition that comprises tear production, conjunctiva, or normal corneal homeostasis.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 3 of 10

Protection of First-Aiders: At minimum, treating personnel should utilize PPE sufficient for prevention of bloodborne pathogen transmission. If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Notes to Physician: Due to irritant properties, resulting from heat created as a solid material dissolves in water, swallowing may result in burns/ulceration of mucus membranes. If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIRE-FIGHTING MEASURES:

- FIRE HAZARD:** This material does not burn
- EXTINGUISHING MEDIA:** Use extinguishing agents appropriate for surrounding fire.
- FIRE-FIGHTING:** Keep unnecessary people away, isolate hazard area and deny entry. This material does not burn. Fight fire for other material that is burning. Water should be applied in large quantities as fine spray. Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Wear protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.
- LOWER FLAMMABILITY LEVEL (air):** Not applicable
- UPPER FLAMMABILITY LEVEL (air):** Not applicable
- FLASH POINT:** Not applicable
- AUTOIGNITION TEMPERATURE:** Not applicable

6. ACCIDENTAL RELEASE MEASURES:

- PERSONAL PRECAUTIONS:** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard on some surfaces. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to Section 7, Handling for additional precautionary measures.
- METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:** Small and large spills: Contain spilled material if possible. Collect in suitable and properly labeled containers. Flush residue with plenty of water. See section 13, Disposal considerations, for additional information.
- ENVIRONMENTAL PRECAUTIONS:** Prevent large spills from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. HANDLING AND STORAGE:

- PRECAUTIONS FOR SAFE HANDLING:** Heat developed during diluting or dissolving of calcium chloride in product is very high. Use cool water when diluting or dissolving (Temperature less than 80°F, 27°C). Avoid contact with eyes, skin and clothing. Do not swallow. Wash thoroughly after handling. See Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 4 of 10

SAFE STORAGE CONDITIONS:

Store in a dry place. Protect from atmospheric moisture. Keep container tightly closed. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

INCOMPATIBILITIES/MATERIALS TO AVOID:

Heat is generated by the calcium chloride in product when mixed with water or aqueous acids. Spattering and boiling can occur. Avoid contact with: bromide trifluoride, 2-furan percarboxylic acid because calcium chloride is incompatible with those substances. Contact with zinc forms flammable hydrogen gas, which can be explosive. Catalyzes exothermic polymerization of methyl vinyl ether. Attacks metals in the presence of moisture, and may release flammable hydrogen gas. Reaction of bromide impurity with oxidizing materials may generate trace levels of impurities such as bromates.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Regulatory Exposure Limit(s):

COMPONENT	CAS NUMBER	OSHA FINAL PEL TWA	OSHA FINAL PEL STEL	OSHA FINAL PEL CEILING
Particulates Not Otherwise Regulated	Not Assigned	TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp)	-----	-----

OEL: Occupational Exposure Level; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Level; TWA: Time Weighted Average; STEL: Short Term Exposure Level

Non-Regulatory Exposure Limit(s):

- The Non-Regulatory United States Occupational Safety and Health Association (OSHA) limits shown in the table are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).
- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

COMPONENT	CAS NUMBER	ACGIH TWA	ACGIH STEL	ACGIH CEILING	OSHA TWA (Vacated)	OSHA STEL (Vacated)	OSHA CEILING (Vacated)
Particulates Not Otherwise Specified (PNOS)	Not Assigned	TWA 10 mg/m ³ (inhalable) TWA 3 mg/m ³ (resp)	-----	-----	-----	-----	-----

Additional Advice: Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

ENGINEERING CONTROLS: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Wear safety glasses with side-shields. For dusty operations or when handling solutions of the material, wear chemical goggles.

SKIN AND BODY PROTECTION: Wear clean, body-covering clothing.

HAND PROTECTION: Use gloves chemically resistant to this material. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures. Examples of preferred glove barrier materials include: Neoprene, Polyvinyl chloride ("PVC" or "vinyl"), Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 5 of 10

workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

RESPIRATORY PROTECTION: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In dusty or misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: High efficiency particulate air (HEPA) N95. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES:

COLOR:	Blend white and pinkish, solid pellets
ODOR:	Odorless
FREEZING POINT/RANGE:	Not applicable to solids
MELTING POINT/RANGE:	772 °C (1,422 °F) Literature Approximately
DECOMPOSITION TEMPERATURE:	Not applicable
VAPOR PRESSURE:	Literature negligible at ambient temperature
VAPOR DENSITY (air=1):	Not applicable
SPECIFIC GRAVITY (water=1):	Not applicable to solids
BULK DENSITY:	58 – 66 lb/ft3 Estimated
WATER SOLUBILITY:	Readily soluble
pH:	Not applicable to solids
FLASH POINT:	Not applicable
LOWER FLAMMABILITY LEVEL (air):	NA
UPPER FLAMMABILITY LEVEL (air):	NA
AUTOIGNITION TEMPERATURE:	Not applicable
HYGROSCOPIC:	Yes

10. STABILITY & REACTIVITY:

REACTIVITY:	Hygroscopic. Liberates large amounts of heat when dissolving in water or aqueous acids.
CHEMICAL STABILITY:	Stable at normal temperatures and pressures.
POSSIBILITY OF HAZARDOUS REACTIONS:	Avoid Moisture.
CONDITIONS TO AVOID:	None known. Avoid moisture.
INCOMPATIBILITIES / MATERIALS TO AVOID:	Heat is generated when mixed with water. Spattering and boiling can occur. Avoid contact with: Sulfuric acid. Corrosive when wet. Flammable hydrogen may be generated from contact with metals such as: Zinc. Sodium. Reaction of bromide impurity with oxidizing materials may generate trace levels of impurities such as bromate.
HAZARDOUS DECOMPOSITION PRODUCTS:	Formed under fire conditions: hydrogen chloride gas, calcium oxide.
HAZARDOUS POLYMERIZATION:	Will not occur.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 6 of 10

11. TOXICOLOGICAL INFORMATION;

TOXICITY DATA:

PRODUCT TOXICITY DATA: CALCIUM CHLORIDE

LD50 Oral: 1055 mg/kg – Oral Acute Toxicity Estimate (ATE)	LD50 Dermal: 2776 mg/kg – Dermal Acute Toxicity Estimate (ATE)	LC50 Inhalation: No data is available
--	--	---

COMPONENT TOXICITY DATA:

Note:

The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given.

Component	LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
Calcium Chloride 10043-52-4	1000 mg/kg (Rat)	2630 mg/kg (Raat)	----
Sodium Chloride 7647-14-5	3 g/kg (Rat)	10 g/kg (Rabbit)	42 g/m ³ (1 hr-Rat)

POTENTIAL HEALTH EFFECTS:

- EYE CONTACT:** For solid: May cause slight eye irritation, mechanical injury only. Dust formation should be avoided, as dust can cause severe eye irritation with corneal injury.
- SKIN CONTACT:** Brief contact is essentially nonirritating to skin. Prolonged contact may cause skin irritation, even a burn. Not classified as corrosive to the skin according to DOT guidelines. May cause more severe response if skin is damp, abraded (scratched or cut), or covered by clothing, gloves or footwear.
- INHALATION:** Dust may cause irritation to upper respirator tract (nose and throat).
- INGESTION:** Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause local mucosal damage to esophagus and stomach. Swallowing may result in gastrointestinal irritation or ulceration.
- CHRONIC EFFECTS:** Chronic exposures to CALCIUM CHLORIDE that cause irritation may cause chronic dermatitis or mucosal membrane problem. For the minor component(s): SODIUM CHLORIDE: Medical experience with sodium chloride has shown a strong association between elevated blood pressure and prolonged dietary overuse. Related effects could occur in the kidneys.

SIGNS AND SYMPTOMS OF EXPOSURE:

Solution and or solids may be visible on the skin and or eyes. Localized redness, warmth, and irritation consistent with mechanism of injury: abrasion, burn, hypertonic solution.

- INHALATION (BREATHING):** Inhaling dust may cause irritation to upper respiratory tract (nose and throat).
- SKIN:** Skin irritation. Direct abrasion of skin from solid, erythema and burn from reaction with water. Prolonged contact and occlusion may cause more severe symptoms. Damage is localized to contact areas.
- EYE:** Eye irritation. Direct abrasion of cornea from solid, erythema and burn from reaction with water, conjunctival swelling and cornea opacification from hypertonic solution and heat.
- INGESTION (SWALLOWING):** Consumption of solids or hypertonic solutions causes nausea, vomiting, and increased thirst.

INTERACTION WITH OTHER CHEMICALS WHICH ENHANCE TOXICITY: None known.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 7 of 10

GHS HEALTH HAZARDS:

GHS: ACUTE TOXICITY – ORAL: Category 4 – Harmful if swallowed.
GHS: ACUTE TOXICITY – DERMAL: Category 5 – May be harmful in contact with skin.
GHS: ACUTE TOXICITY – INHALATION: No data available. Not classified.
GHS: CONTACT HAZARD – SKIN: Category 2 – Causes skin irritation.
GHS: CONTACT HAZARD – EYE: Category 2B – Causes eye irritation.
GHS: CARCINOGENICITY: Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC, or OSHA.

MUTAGENIC DATA: Not classified as a mutagen per GHS criteria.
Calcium chloride (CaCl₂) – In vitro genetic toxicity studies were negative.
Sodium Chloride – In vitro genetic toxicity studies were predominately negative.

DEVELOPMENTAL TOXICITY:

Not classified as a development or reproductive toxin per GHS criteria.
For the major component(s): Did not cause birth defects or any other fetal effects in laboratory animals.

12. ECOLOGICAL INFORMATION;

ECOTOXICITY DATA:

Aquatic Toxicity: Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested)

Freshwater Fish Toxicity:

Calcium Chloride: LC50, bluegill (*Lepomis macrochirus*): 8,350 - 10,650 mg/l
Potassium Chloride: LC50, rainbow trout (*Oncorhynchus mykiss*), 96h: 4,236 mg/l
Sodium Chloride: LC50, fathead minnow (*Pimephales promelas*): 10,610 mg/l

Invertebrate Toxicity:

Calcium Chloride: LC50, water flea *Daphnia magna*: 759 - 3,005 mg/l
Potassium Chloride: EC50, water flea *Daphnia magna*, 24 h, immobilization: 590 mg/l
LC50, water flea *Ceriodaphnia dubia*, 96 h: 3,470 mg/l
Sodium Chloride: LC50, water flea *Daphnia magna*: 4,571 mg/l

Microorganism Toxicity:

Sodium Chloride: IC50, OECD 209 Test; activated sludge, respiration inhibition: > 1,000 mg/l

FATE AND TRANSPORT:

BIODEGRADATION: This material is inorganic and not subject to biodegradation

PERSISTENCE: Calcium chloride is believed not to persist in the environment because it is readily dissociated into calcium and chloride ions in water. Calcium chloride released into the environment is thus likely to be distributed into water in the form of calcium and chloride ions. Calcium ions may remain in soil by binding to soil particulate or by forming stable salts with other ions. Chloride ions are mobile and eventually drain into surface water. Both ions originally exist in nature, and their concentrations in surface water will depend on various factors, such as geological parameters, weathering and human activities.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 8 of 10

BIOCONCENTRATION: No bioconcentration is expected because of the relatively high water solubility. Potential for mobility in soil is very high (Koc between 0 and 50). Partitioning from water to n-octanol is not applicable.

BIOACCUMULATIVE POTENTIAL: Calcium chloride and its dissociated forms (calcium and chloride ions) are ubiquitous in the environment. Calcium and chloride ions can also be found as constituents in organisms. Considering its dissociation properties, calcium chloride is not expected to accumulate in living organisms.

MOBILITY IN SOIL: Calcium chloride is not expected to be absorbed in soil due to its dissociation properties and high water solubility. It is expected to dissociate into calcium and chloride free ions or it may form stable inorganic or organic salts with other counter ions, leading to different fates between calcium and chloride ions in soil and water components. Calcium ions may bind to soil particulate or may form stable inorganic salts with sulfate and carbonate ions. The chloride ion is mobile in soil and eventually drains into surface water because it is readily dissolved in water.

13. DISPOSAL CONSIDERATIONS: (See Section 14 for Regulatory Information)

WASTE FROM MATERIAL:

Reuse or reprocess, if possible. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Report spills if applicable. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Landfill and waste water treatment system.

CONTAINER MANAGEMENT:

Dispose of container in accordance with applicable local, regional, national and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

14. TRANSPORT INFORMATION:

UNITED STATES DOT INFORMATION:

This product is not regulated by D.O.T. when shipped domestically by land.

CANADIAN TDG INFORMATION:

This product is not regulated by T.D.G. when shipped domestically by land.

15. REGULATORY INFORMATION: (Not meant to be all-inclusive- selected regulations represented)

D.O.T. PROPER SHIPPING NAME:	N/A
HAZARDOUS SUBSTANCE 49CFR CERCLA:	N/A
D.O.T. HAZARD CLASS	N/A
D.O.T. LABELS REQUIRED	N/A
D.O.T. PLACARDS REQUIRED	N/A



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 9 of 10

U.S. REGULATIONS

OSHA REGULATORY STATUS:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) (US)

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

Not regulated

EPCRA EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30):

Not regulated

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.21):

Acute Health Hazard

EPCRA SECTION 313 (40 CFR 372.65):

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

OSHA PROCESS SAFETY (PSM) (29 CFR 372.65):

Not regulated

NATIONAL INVENTORY STATUS

U.S. INVENTORY STATUS: TOXIC SUBSTANCE CONTROL ACT (TSCA):

All components are listed or exempt

TSCA 12(b):

This product is not subject to export notification

CANADIAN CHEMICAL INVENTORY:

All components are listed

STATE REGULATIONS

CALIFORNIA PROPOSITION 65:

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute. **WARNING:** This product (when used in aqueous formulations with a chemical oxidizer such as ozone) may react to form calcium bromate, a chemical known to the State of California to cause cancer.

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

WHMIS INFORMATION:

The Canadian Workplace Hazardous Materials Information System (WHMIS) Classification for this product is:

D2B – eye or skin irritant (See sections 4 & 5) Refer to employer's workplace education program.



EMERGENCY PHONE: 800-553-8011

Effective date: 06/01/2015

Print date: 5/29/2015

NFPA: Health 1, Fire 0, Reactivity 0

Page 10 of 10

16. OTHER INFORMATION:

HMS: (SCALE 0-4) (Rated using National Paint & Coatings Association HMS: Rating Instructions, 2nd Edition)

HEALTH RATING: 2 FLAMMABILITY RATING: 0 REACTIVE RATING: 0

NFPA 704 – HAZARD IDENTIFICATION RATINGS (SCALE 0-4)

HEALTH RATING: 1 FLAMMABILITY RATING: 0 REACTIVE RATING: 0

ADDITIONAL HEALTH DATA COMMENT:

This Safety Data Sheet contains environmental, health and toxicological information for your employees. Please make sure this information is given to them. It also contains information to help you meet community right-to-know / emergency response reporting requirements under SARA Title III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS. Discard any previous edition of this SDS.

Latest version of this SDS can be found at <http://www.OSSIAN.com>

IMPORTANT:

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Ossian Inc. makes no representations as to its accuracy or sufficiency. **NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE BY OSSIAN INC. REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE.** This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Ossian assumes no liability whatsoever for the use of or reliance upon this information. Conditions of use are beyond Ossian's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Ossian Inc, assumes no responsibility for any injury or loss resulting from the use of the product described herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in the Safety Data Sheet available to your employees.